

Safety Data Sheet

Supplies For Candles LTD. Swinton Bridge Industrial Estate Whitelee Road, Swinton, South Yorkshire, S64 8BH, UK

Tel: 01709 257 151

Coco Pro Nature Wax NatureWax 660-55M

This document is intended to provide information about the current product specification. Only when signed by the customer does it constitute to an agreed specification. Otherwise, this product data sheet should be considered as indicative, and may be subject to change.

If you have questions, please contact customerservice@suppliesforcandles.co.uk

Description

Product Description

This product is based on refined vegetable triglycerides of non-GM origin. All NatureWax products comply with the requirements of the Quality Association for Candles, as detailed in directive RAL-GZ 041 (Appendix I, Section IV).

THIS IS A DRAFT VERSION OF THE SPECIFICATION. TECHNICAL SPECIFICATIONS ARE DEFINED AS TYPICAL VALUES AND ARE SUBJECT TO REVISION / AMENDMENT AFTER APPROXIMATELY 10 PRODUCTIONS.

Analyses and specifications

- The specification for quality is final at loading in compliance with all Trading rules.
- Cargill reserves the right to use internal analytical methods that are in compliance with the International Reference Methods.

Quality and Chemical Parameters

		Min	Тур.	Max	UoM	Method
Colour Red	Lov. 5 1/4"			1.5		ISO 15305
Colour Yellow	Lov. 5 1/4"			15		ISO 15305

Quality and Chemical Parameters - Conformity

		Min	Тур.	Max	UoM	Method
Free Fatty Acids	as oleic (282)			0.5	%	ISO 660
Moisture Content	Karl Fisher			0.05	%	ISO 8534
Peroxide Value	at loading			1	meq/kg	ISO 3960

Physical Parameters

		Min	Тур.	Max	UoM	Method
Solid Fat Content	at 20 °C	88		94	%	pNMR
Solid Fat Content	at 30 °C	69		75	%	pNMR
Solid Fat Content	at 40 °C	34		40	%	pNMR

Physical Parameters - Conformity

	Min	Тур.	Max	UoM	Method
Melting Point -		48		°C	NEN 6313

Page 1 of 2

Above mentioned analytical parameters are printed on the certificate of analysis (CoA).



Safety Data Sheet

Supplies For Candles LTD. Swinton Bridge Industrial Estate Whitelee Road,Swinton ,South Yorkshire, S64 8BH, UK

Tel: 01709 257 151

Coco Pro Nature Wax NatureWax 660-55M

Additional	Product Infor	mation
Auuiliviiai	PIOUULL IIIIOI	IIIALIUII

Batch code

Each order has a unique loading order number.

REACH

This product complies fully with REACH (EC) regulation No 1907/2006.

Packaging and Storage Information/Recommendations

Recommended storage conditions

Bulk

Bulk storage temperature at customer's site *	10-15°C above melting temperature
---	-----------------------------------

For more information on the NatureWax - Range please visit our webpages

Signature

Herewith the customer confirms to agree with above mentioned specification:
Customer:
Name and function:
E-mail address:
Date:
Signature:
Disclaimer:

This document is provided for your information and convenience only. All information, statements, recommendations and suggestions are believed to be true and accurate under local laws but are made without guarantee, express or implied. WE DISCLAIM, TO THE FULLEST EXTENT PERMITTED BY LAW, ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE and FREEDOM FROM INFRINGEMENT and disclaim all liability in connection with the storage, handling or use of our products or information, statements, recommendations and suggestions contained herein. All such risks are assumed by you/user. The labeling, substantiation and decision making relating to the regulatory approval status of, the labeling on and claims for your products is your responsibility. We recommend you consult regulatory and legal advisors familiar with applicable laws, rules and regulations prior to making regulatory, labeling or claims decisions for your products. The information, statements, recommendations and suggestions contained herein are subject to change without notice.

 Issue date
 19-May-2020
 Page 2 of 2
 Specification [Rev] : BL00010666 [2]

^{*} Loading / delivery temperature can be different from recommended storage conditions due to technical reasons.