

Version: 1 (28/09/2021)

## SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

**Product:** CRACKLING LOG FIRE FRAG0326 @10% IN NON HAZARDOUS BASE

Version: 1

Section 1. Identification of the substance or the mixture and of the supplier

1.1 Product Identifier

**Product identifier:** CRACKLING LOG FIRE FRAG0326 @10% IN NON HAZARDOUS BASE

Other identifiers: None

1.2 Relevant identified uses of the substance of mixture and uses advised against

**Product uses:** Fragrances

1.3 Details of the supplier of the safety data sheet

Supplies For Candles LTD. Company name: Company address: Swinton Bridge Industrial Estate

Whitelee Road

Swinton

South Yorkshire

S64 8BH UK

Contact: Nicky Story

E-Mail address: customerservice@suppliesforcandles.co.uk

Company phone: 01709 257151 1.4 Emergency telephone number

**Emergency phone:** 01709 257151

Section 2. Hazards identification

2.1 Classification of the substance or mixture

Classification under Regulation (EC) No 1272/2008

danger:

Class and category of Hazardous to the Aquatic Environment - Long-term Hazard Category 2

H411, Toxic to aquatic life with long lasting effects.

2.2 Label elements

Classification under Regulation (EC) No 1272/2008

Signal word: None

**Hazard statements:** H411, Toxic to aquatic life with long lasting effects.

Supplemental EUH208, Contains BOISAMBRENE FORTE ex stort / AMBERWOOD F ex symrise b/n2144,

GUAIACWOOD B/N:C9625, ISO E SUPER. May produce an allergic reaction. Information:

**Precautionary** P273, Avoid release to the environment.

statements: P391, Collect spillage.

P501, Dispose of contents/container to approved disposal site, in accordance with local



Version: 1 (28/09/2021)

## SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

**Product:** CRACKLING LOG FIRE FRAG0326 @10% IN NON HAZARDOUS BASE

Version: 1

regulations.

Pictograms:



#### 2.3 Other hazards

Other hazards: None

## Section 3. Composition / information on ingredients

#### 3.2 Mixtures

### **Contains:**

Name	CAS	EC	REACH Registration No.	%	Classification for (CLP) 1272/2008
Tonalid	1506-02-1	216-133-4		12 1/1%	ATO 4-EH A1-EH C1; H302-H410,-
GUAIACWOOD B/N: C9625	8016-23-7	289-632-8		10 70%	SCI 2-SS 1B-EH C2; H315-H317-H411,-
alpha-Cedrene	469-61-4	207-418-4		11 /1 30/2	AH 1-EH A1-EH C1; H304-H410,-
ISO E SUPER	54464-57-2	259-174-3		111 '7/10/2	SCI 2-SS 1B-EH C1; H315-H317-H410,-
BOISAMBRENE FORTE ex stort / AMBERWOOD F ex symrise b/n2144				111 .7.30%	SCI 2-SS 1B-EH C2; H315-H317-H411,-

## **Substances with Community workplace exposure limits:**

Not Applicable

Substances that are persistent, bioaccumulative and toxic or very persistent and very bioaccumulative, greater than 0.1%:

Not Applicable

## Section 4. First-aid measures

### 4.1 Description of first aid measures

Inhalation: Remove from exposure site to fresh air, keep at rest, and obtain medical attention.

Eye exposure: Flush immediately with water for at least 15 minutes. Contact physician if symptoms persist. Remove contaminated clothes. Wash thoroughly with soap and water. Contact physician if Skin exposure:

irritation persists.

Rinse mouth with water and obtain medical attention. Ingestion:



· SFC ·

Issue date: 28/09/2021 Version: 1 (28/09/2021)

## SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

Product: CRACKLING LOG FIRE FRAG0326 @10% IN NON HAZARDOUS BASE

Version: 1

### 4.2 Most important symptoms and effects, both acute and delayed

None expected, see Section 4.1 for further information.

### 4.3 Indication of any immediate medical attention and special treatment needed

None expected, see Section 4.1 for further information.

### **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

Suitable media: Carbon dioxide, Dry chemical, Foam.

### 5.2 Special hazards arising from the substance or mixture

In case of fire, may be liberated: Carbon monoxide, Unidentified organic compounds.

#### 5.3 Advice for fire fighters:

In case of insufficient ventilation, wear suitable respiratory equipment.

### Section 6. Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures:

Avoid inhalation. Avoid contact with skin and eyes. See protective measures under Section 7 and 8.

#### 6.2 Environmental precautions:

Keep away from drains, surface and ground water, and soil.

### 6.3 Methods and material for containment and cleaning up:

Remove ignition sources. Provide adequate ventilation. Avoid excessive inhalation of vapours. Contain spillage immediately by use of sand or inert powder. Dispose of according to local regulations.

### 6.4 Reference to other sections:

Also refer to sections 8 and 13.

### Section 7. Handling and storage

#### 7.1 Precautions for safe handling:

Keep away from heat, sparks, open flames and hot surfaces. - No smoking. Use personal protective equipment as required. Use in accordance with good manufacturing and industrial hygiene practices. Use in areas with adequate ventilation. Do not eat, drink or smoke when using this product.

### 7.2 Conditions for safe storage, including any incompatibilities:

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use only non-sparking tools. Take





Version: 1 (28/09/2021)

## SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

**Product:** CRACKLING LOG FIRE FRAG0326 @10% IN NON HAZARDOUS BASE

Version: 1

precautionary measures against static discharge.

### 7.3 Specific end use(s):

Fragrances: Use in accordance with good manufacturing and industrial hygiene practices.

### Section 8. Exposure controls/personal protection

### 8.1 Control parameters

Workplace exposure limits: Not Applicable

#### **8.2 Exposure Controls**

#### **Eye / Skin Protection**

Wear protective gloves/eye protection/face protection

### **Respiratory Protection**

Under normal conditions of use and where adequate ventilation is available to prevent build up of excessive vapour, this material should not require special engineering controls. However, in conditions of high or prolonged use, or high temperature or other conditions which increase exposure, the following engineering controls can be used to minimise exposure to personnel: a) Increase ventilation of the area with local exhaust ventilation. b) Personnel can use an approved, appropriately fitted respirator with organic vapour cartridge or canisters and particulate filters. c) Use closed systems for transferring and processing this material.

Also refer to Sections 2 and 7.

### Section 9. Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance: Not determined Odour: Not determined **Odour threshold:** Not determined :Ha Not determined **Melting point / freezing point:** Not determined Not determined Initial boiling point / range:

> 60 °C Flash point:

**Evaporation rate:** Not determined Flammability (solid, gas): Not determined

**Upper/lower flammability or explosive limits:** Product does not present an explosion hazard

Vapour pressure: Not determined Vapour density: Not determined Not determined Relative density: Solubility(ies): Not determined Partition coefficient: n-octanol/water: Not determined **Auto-ignition temperature:** Not determined



Version: 1 (28/09/2021)

## SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

**Product:** CRACKLING LOG FIRE FRAG0326 @10% IN NON HAZARDOUS BASE

Version: 1

**Decomposition temperature:** Not determined Viscosity: Not determined **Explosive properties:** Not expected Oxidising properties: Not expected

9.2 Other information: None available

## Section 10. Stability and reactivity

### 10.1 Reactivity:

Presents no significant reactivity hazard, by itself or in contact with water.

#### 10.2 Chemical stability:

Good stability under normal storage conditions.

### 10.3 Possibility of hazardous reactions:

Not expected under normal conditions of use.

#### 10.4 Conditions to avoid:

Avoid extreme heat.

#### 10.5 Incompatible materials:

Avoid contact with strong acids, alkalis or oxidising agents.

## 10.6 Hazardous decomposition products:

Not expected.

### Section 11. Toxicological information

### 11.1 Information on toxicological effects

This mixture has not been tested as a whole for health effects. The health effects have been calculated using the methods outlined in Regulation (EC) No 1272/2008 (CLP).

This material does not meet the criteria for classification for health hazards under Regulation (EC) No 1272/2008.

**Acute Toxicity:** Based on available data the classification criteria are not met.

>5000 Acute Toxicity Oral

Not Applicable **Acute Toxicity Dermal** Acute Toxicity Inhalation Not Available

Skin corrosion/irritation: Based on available data the classification criteria are not met. Based on available data the classification criteria are not met. Serious eye damage/irritation: Respiratory or skin sensitisation: Based on available data the classification criteria are not met. Germ cell mutagenicity: Based on available data the classification criteria are not met. Based on available data the classification criteria are not met. Carcinogenicity: Reproductive toxicity: Based on available data the classification criteria are not met. STOT-single exposure: Based on available data the classification criteria are not met. Based on available data the classification criteria are not met. STOT-repeated exposure:



Page 6 (8)

Issue date: 28/09/2021

Version: 1 (28/09/2021)

## **SAFETY DATA SHEET**

In accordance with REACH Regulation EC No.1907/2006

Product: CRACKLING LOG FIRE FRAG0326 @10% IN NON HAZARDOUS BASE

Version: 1

**Aspiration hazard:** Based on available data the classification criteria are not met.

## Information about hazardous ingredients in the mixture

Ingredient	CAS	EC	LD50/ATE Oral	LD50/ATE Dermal	LC50/ATE Inhalation	LC50 Route
Tonalid	1506-02-1	216-133-4	1000	Not available	INOT available	Not available

Refer to Sections 2 and 3 for additional information.

## Section 12. Ecological information

12.1 Toxicity:

Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability:Not available12.3 Bioaccumulative potential:Not available12.4 Mobility in soil:Not available

12.5 Results of PBT and vPvB assessment:

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

**12.6 Other adverse effects:** Not available

### Section 13. Disposal considerations

### 13.1 Waste treatment methods:

Dispose of in accordance with local regulations. Avoid disposing into drainage systems and into the environment. Empty containers should be taken to an approved waste handling site for recycling or disposal.

## **Section 14. Transport information**

**14.1 UN number:** UN3082

**14.2 UN Proper Shipping Name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(alpha-Cedrene, Tonalid)

**14.3 Transport hazard class(es):** 9

Sub Risk: -

14.4. Packing Group:

**14.5 Environmental hazards:** This is an environmentally hazardous substance.

**14.6 Special precautions for user:** None additional

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:

Not applicable

### **Section 15. Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

None additional



·SFC·

Issue date: 28/09/2021 Version: 1 (28/09/2021)

# **SAFETY DATA SHEET**

In accordance with REACH Regulation EC No.1907/2006

Product: CRACKLING LOG FIRE FRAG0326 @10% IN NON HAZARDOUS BASE

Version: 1

## 15.2 Chemical Safety Assessment

A Chemical Safety Assessment has not been carried out for this product.

**Section 16. Other information** 

Concentration % Limits: EH C2=37.24% EH C3=3.72%

Total Fractional Values: EH C2=2.69 EH C3=26.85

Key to revisions:

Not applicable

# Key to abbreviations:

Abbreviation	Meaning		
AH 1	Aspiration Hazard Category 1		
ATO 4	Acute Toxicity - Oral Category 4		
EH A1	Hazardous to the Aquatic Environment - Acute Hazard Category 1		
EH C1	Hazardous to the Aquatic Environment - Long-term Hazard Category 1		
EH C2	Hazardous to the Aquatic Environment - Long-term Hazard Category 2		
H302	Harmful if swallowed.		
H304	May be fatal if swallowed and enters airways.		
H315	Causes skin irritation.		
H317	May cause an allergic skin reaction.		
H410	Very toxic to aquatic life with long lasting effects.		
H411	Toxic to aquatic life with long lasting effects.		
P261	Avoid breathing vapour or dust.		
P264	Wash hands and other contacted skin thoroughly after handling.		
P270	Do not eat, drink or smoke when using this product.		
P272	Contaminated work clothing should not be allowed out of the workplace.		
P273	Avoid release to the environment.		
P280	Wear protective gloves/eye protection/face protection.		
P301/310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.		
P301/312	IF SWALLOWED: call a POISON CENTER or doctor/physician if you feel unwell.		
P302/352	IF ON SKIN: Wash with plenty of soap and water.		
P330	Rinse mouth.		
P331	Do not induce vomiting.		
P333/313	If skin irritation or rash occurs: Get medical advice/attention.		
P362	Take off contaminated clothing and wash before reuse.		
P391	Collect spillage.		
P405	Store locked up.		
P501	Dispose of contents/container to approved disposal site, in accordance with local regulations.		
SCI 2	Skin Corrosion / Irritation Category 2		
SS 1B	Sensitization - Skin Category 1B		



·SFC·

Issue date: 28/09/2021

Version: 1 (28/09/2021)

# **SAFETY DATA SHEET**

In accordance with REACH Regulation EC No.1907/2006

Product: CRACKLING LOG FIRE FRAG0326 @10% IN NON HAZARDOUS BASE

Version: 1

The information in this safety data sheet is to the best of our knowledge true and accurate but all data, instructions, recommendations and/or suggestions are made without guarantee.