



SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

Product: FRAGRANCE FF1906, 10% \$190638710%

Version: 1

Section 1. Identification of the substance or the mixture and of the supplier

1.1 Product Identifier

Product identifier: FRAGRANCE FF1906, 10% \$190638710%(Contains:ISO E SUPER)

Other identifiers: None

1.2 Relevant identified uses of the substance of mixture and uses advised against

Product uses: Fragrances

1.3 Details of the supplier of the safety data sheet

Company name: Supplies For Candles

Company address: Unit E Swinton Bridge Industrial Estate, Whitelee Road, Swinton, Rotherham, S64 8BH

Contact: Nicky Story

E-Mail address: info@SuppliesForCandles.co.uk

Company phone: +44 1709 588579 1.4 Emergency telephone number

Emergency phone: +44 1709 588579

Section 2. Hazards identification

2.1 Classification of the substance or mixture

Classification under Regulation (EC) No 1272/2008

Class and category of Sensitization - Skin Category 1

danger:

Hazardous to the Aquatic Environment - Long-term Hazard Category 2

H317, May cause an allergic skin reaction.


H411, Toxic to aquatic life with long lasting effects.

Classification under Directive 1999/45/EC

Hazard symbols: Xi, Irritant.

Risk phrases: R43, May cause sensitisation by skin contact.

R52/53, Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic





						Varaian: 1 (24/10/2016)
			SAFETY DATA	SHEET		
		In accordar	ice with REACH Regu	ation EC No).1907/2006	
	GRANCE F	F1906, 109	6 \$190638710%			
BRASSYLATE (MUSK	105-95-3	203-347-8		0.37%	N ; R51/53	
T93)						
	L				L	SCI 2-EDI 2-SS 1B-EH C2;
CASHMERAN	33704-61-9	251-649-3		0.23%	XI-N; R43-R36/38-R51/53	H315-H317-H319-H411,-
Xn-N ; R10-R38-R43-R6	5limonene	5989-27-5	227-813-5	0.22% A1-E	H C1;H226-H304- R50/53	FL 3-SCI 2-SS 1B-AH 1-EH
alpha ise methyl						H315-H317-H410,- SCI 2 SS 1B EH C2:H315
	127-51-5	204-846-3		0.17%	Xi-N; R43-R36/38-R51/53	0012 00 15 211 02,11010
onone						H317-H411,-
helional	1205-17-0	214-881-6		0.17%	Xi-N; R43-R51/53	SS 1B-EH C2;H317-H411,
Version: 1						
bangalol	28219-61-6	248-908-8		0.12%	Xi-N; R36-R50/53	EDI 2-EH A1-EH C1;H319- H410,-
PATCHOULI OIL POGOSTEMON CABLIN	8014-09-3	282-493-4		0.03%	N ; R51/53	AH 1-EH C2;H304-H411,-
pinenes	80-56-8	201-291-9		0.02%	Xn ; R10-R38-R43-R65	FL 3-SCI 2-SS 1B-AH 1; H226-H304-H315-H317,-
Gamma-Terpinene	99-85-4	202-794-6		0.01%	Xn ; R10-R65	FL 3-AH 1;H226-H304,-
Myrcene	123-35-3	204-622-5		0.005%	Xn ; R10-R38-R65	FL 3-SCI 2-EDI 2-AH 1; H226-H304-H315-H319,-
patchouli oil light	8014-09-3	282-493-4		0.003%	N ; R51/53	AH 1-EH C2;H304-H411,-
Beta-Caryophyllene	87-44-5	201-746-1		<0.001%	Xn ; R65	AH 1;H304,-

Substances with Community workplace exposure limits, not listed above:

Not Applicable

Substances that are persistent, bioaccumulative and toxic or very persistent and very bioaccumulative, greater than

0.1%: Not Applicable

Section 4. First-aid measures

4.1 Description of first aid measures

IF ON SKIN: Wash with plenty of soap and water.

4.2 Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.


4.3 Indication of any immediate medical attention and special treatment needed

None expected, see Section 4.1 for further information.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable media: Carbon dioxide, Dry chemical, Foam.





SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

Product: FRAGRANCE FF1906, 10% \$190638710% 5.2 Special hazards arising from the substance or mixture

In case of fire, may be liberated: Carbon monoxide, Unidentified organic compounds.

5.3 Advice for fire fighters:

In case of insufficient ventilation, wear suitable respiratory equipment.

Section 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Avoid inhalation. Avoid contact with skin and eyes. See protective measures under Section 7 and 8.

Version: 1

6.2 Environmental precautions:

Keep away from drains, surface and ground water, and soil.

6.3 Methods and material for containment and cleaning up:

Remove ignition sources. Provide adequate ventilation. Avoid excessive inhalation of vapours. Contain spillage immediately by use of sand or inert powder. Dispose of according to local regulations.

6.4 Reference to other sections:

Also refer to sections 8 and 13.

Section 7. Handling and storage

7.1 Precautions for safe handling:

Keep away from heat, sparks, open flames and hot surfaces. - No smoking. Use personal protective equipment as required. Use in accordance with good manufacturing and industrial hygiene practices. Use in areas with adequate ventilation Do not eat, drink or smoke when using this product.

7.2 Conditions for safe storage, including any incompatibilities:

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.


7.3 Specific end use(s):

Fragrances: Use in accordance with good manufacturing and industrial hygiene practices.

Section 8. Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limits: Not Applicable





SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

Product: FRAGRANCE FF1906, 10% \$190638710%

8.2 Exposure Controls

Eye / Skin Protection

Wear protective gloves/eye protection/face protection

Respiratory Protection

Under normal conditions of use and where adequate ventilation is available to prevent build up of excessive vapour, this material should not require special engineering controls. However, in conditions of high or prolonged use, or high temperature or other conditions which increase exposure, the following engineering controls can be used to minimise exposure to personnel: a) Increase ventilation of the area with local exhaust ventilation. b) Personnel can use an approved, appropriately fitted respirator with organic vapour cartridge or canisters and particulate filters. c) Use closed systems for transferring and processing this material. Also refer to Sections 2 and 7.

Version: 1

Section 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties
Appearance: Not determined
Odour: Not determined
pH: Not determined
Initial boiling point / range: Not determined

Flash point: > 70 °C

Vapour pressure:

Relative density:

Solubility(ies):

9.2 Other information:

Not determined

Not determined

Not determined

Section 10. Stability and reactivity

10.1 Reactivity:

Presents no significant reactivity hazard, by itself or in contact with water.

10.2 Chemical stability:

Good stability under normal storage conditions.

10.3 Possibility of hazardous reactions:

Not expected under normal conditions of use.


10.4 Conditions to avoid:

Avoid extreme heat.

10.5 Incompatible materials:

Avoid contact with strong acids, alkalis or oxidising agents.

10.6 Hazardous decomposition products:





SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

Product: FRAGRANCE FF1906, 10% \$190638710%

Not expected.

Section 11. Toxicological information

11.1 Information on toxicological effects

This mixture has not been tested as a whole for health effects. The health effects have been calculated using the methods outlined in Regulation (EC) No 1272/2008 (CLP).

May cause an allergic skin reaction.

Assumed Toxicity Value (LD50 or ATE) for Acute Oral Toxicity:

Assumed Toxicity Value (LD50 or ATE) for Acute Dermal Toxicity:

Not Applicable

Not Applicable

Assumed Toxicity Value (LC50 or ATE) for Acute Inhalation Toxicity:

Not Available

Version: 1

Inhalation Route: Not Available

Information about hazardous ingredients in the mixture

Not Applicable

Refer to Sections 2 and 3 for additional information.

Section 12. Ecological information

12.1 Toxicity:

Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability: Not available

12.3 Bioaccumulative potential: Not available 12.4 Mobility in

soil: Not available

12.5 Results of PBT and vPvB assessment:

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

12.6 Other adverse effects: Not available


Section 13. Disposal considerations

13.1 Waste treatment methods:

Dispose of in accordance with local regulations. Avoid disposing into drainage systems and into the environment. Empty containers should be taken to an approved waste handling site for recycling or disposal.

Section 14. Transport information

14.1 UN number: UN3082





SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

Product: FRAGRANCE FF1906, 10% \$190638710%

14.2 UN Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ISO

E SUPER, GALAXOLIDE 50 DEP)

14.3 Transport hazard class(es): 9

Sub Risk: -

14.4. Packing Group:

14.5 Environmental hazards: This is an environmentally hazardous substance.

14.6 Special precautions for user: None additional

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:

Not applicable

Section 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

None additional

Version: 1

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has not been carried out for this product.


Section 16. Other information

Concentration % Limits: EH C2=71.94% EH C3=7.19% SS 1=37.64%

Total Fractional Values: EH C2=1.39 EH C3=13.90 SS 1=2.66

Key to revisions:

Not applicable





SAFETY DATA SHEET


In accordance with REACH Regulation EC No.1907/2006

Product: FRAGRANCE FF1906, 10% \$190638710%

Key to abbreviations:

AH 1 Aspiration Hazard Category 1 EDI 2 Eye Damage / Irritation Category 2 EH At1 Hazardous to the Aquatic Environment - Acute Hazard Category 1 EH C1 Hazardous to the Aquatic Environment - Long-term Hazard Category 1 EH C2 Hazardous to the Aquatic Environment - Long-term Hazard Category 2 EH C3 Hazardous to the Aquatic Environment - Long-term Hazard Category 2 EH C3 Hazardous to the Aquatic Environment - Long-term Hazard Category 3 FL3 Flammable Liquid, Hazard Category 3 FL3 Flammable liquid and vapour. H340 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H310 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. P210 Keep away from heat, sparks, open flames and hot surfaces No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe vapour or dust. P264 Wash hands and other contacted skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P271 Containing the surfaces to the environment. P272 Avoid treating a value for the surfaces to the overloament.	Abbreviation	Meaning	
EH A1 Hazardous to the Aquatic Environment - Acute Hazard Category 1 EH C1 Hazardous to the Aquatic Environment - Long-term Hazard Category 2 EH C2 Hazardous to the Aquatic Environment - Long-term Hazard Category 2 EH C3 Hazardous to the Aquatic Environment - Long-term Hazard Category 3 FL 3 Flammable Liquid, Hazard Category 3 FL 3 Flammable Liquid, Hazard Category 3 Haze6 Flammable Liquid, Hazard Category 3 Haze6 Flammable Liquid and vapour. Ha304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H310 Way cause damage to organs (organs, exposure route). H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H210 Keep away from heat, sparks, open flames and hot surfaces No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe vapour or dust. P264 Wash hands and other contacted skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace.	AH 1	Aspiration Hazard Category 1	
EH C1 Hazardous to the Aquatic Environment - Long-term Hazard Category 1 EH C2 Hazardous to the Aquatic Environment - Long-term Hazard Category 2 EH C3 Hazardous to the Aquatic Environment - Long-term Hazard Category 3 FL 3 Flammable Liquid, Hazard Category 3 FL 3 Flammable Liquid, Hazard Category 3 H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H319 Causes serious eye irritation. H310 Very toxic to aquatic life with long lasting effects. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. H210 Keep away from heat, sparks, open flames and hot surfaces No smoking. H223 Keep container tightly closed. H240 Ground/bond container and receiving equipment. H241 Use explosion-proof electrical, ventilating and lighting equipment. H242 Use only non-sparking tools. H243 Take precautionary measures against static discharge. H244 Do not breathe vapour or dust. H245 Avoid breathing vapour or dust. H264 Wash hands and other contacted skin thoroughly after handling. H270 Do not eat, drink or smoke when using this product. H271 Contaminated work clothing should not be allowed out of the workplace.	EDI 2	Eye Damage / Irritation Category 2	
EH C2 Hazardous to the Aquatic Environment - Long-term Hazard Category 2 EH C3 Hazardous to the Aquatic Environment - Long-term Hazard Category 3 FL 3 Flammable Liquid, Hazard Category 3 H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H319 Causes serious eye irritation. H311 May cause damage to organs (organs, exposure route). H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. H210 Keep away from heat, sparks, open flames and hot surfaces No smoking. H223 Keep container tightly closed. H241 Use explosion-proof electrical, ventilating and lighting equipment. H242 Use only non-sparking tools. H243 Take precautionary measures against static discharge. H240 Do not breathe vapour or dust. H264 Wash hands and other contacted skin thoroughly after handling. H270 Do not eat, drink or smoke when using this product. H271 Contaminated work clothing should not be allowed out of the workplace.	EH A1	Hazardous to the Aquatic Environment - Acute Hazard Category 1	
EH C3 Hazardous to the Aquatic Environment - Long-term Hazard Category 3 FL 3 Flammable Liquid, Hazard Category 3 H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H311 May cause damage to organs (organs, exposure route). H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. H210 Keep away from heat, sparks, open flames and hot surfaces No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe vapour or dust. P261 Avoid breathing vapour or dust. P262 Wash hands and other contacted skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment.	EH C1	Hazardous to the Aquatic Environment - Long-term Hazard Category 1	
FL 3 Flammable Liquid, Hazard Category 3 H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H310 Way cause damage to organs (organs, exposure route). H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. H412 Keep away from heat, sparks, open flames and hot surfaces No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe vapour or dust. P261 Avoid breathing vapour or dust. P264 Wash hands and other contacted skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace.	EH C2	Hazardous to the Aquatic Environment - Long-term Hazard Category 2	
H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H310 Way cause damage to organs (organs, exposure route). H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. H210 Keep away from heat, sparks, open flames and hot surfaces No smoking. H233 Keep container tightly closed. H241 Use explosion-proof electrical, ventilating and lighting equipment. H242 Use only non-sparking tools. H243 Take precautionary measures against static discharge. H260 Do not breathe vapour or dust. H264 Wash hands and other contacted skin thoroughly after handling. H270 Do not eat, drink or smoke when using this product. H272 Contaminated work clothing should not be allowed out of the workplace.	EH C3	Hazardous to the Aquatic Environment - Long-term Hazard Category 3	
H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H310 Way cause damage to organs (organs, exposure route). H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. P210 Keep away from heat, sparks, open flames and hot surfaces No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe vapour or dust. P261 Avoid breathing vapour or dust. P264 Wash hands and other contacted skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment.	FL 3	Flammable Liquid, Hazard Category 3	
H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H371 May cause damage to organs (organs, exposure route). H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmfult to aquatic life with long lasting effects. H210 Keep away from heat, sparks, open flames and hot surfaces No smoking. H233 Keep container tightly closed. H240 Ground/bond container and receiving equipment. H241 Use explosion-proof electrical, ventilating and lighting equipment. H242 Use only non-sparking tools. H243 Take precautionary measures against static discharge. H260 Do not breathe vapour or dust. H261 Avoid breathing vapour or dust. H262 Contaminated work clothing should not be allowed out of the workplace. H272 Contaminated work clothing should not be allowed out of the workplace. H273 Avoid release to the environment.	H226	Flammable liquid and vapour.	
H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H371 May cause damage to organs (organs, exposure route). H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. P210 Keep away from heat, sparks, open flames and hot surfaces No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe vapour or dust. P261 Avoid breathing vapour or dust. P264 Wash hands and other contacted skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment.	H304	May be fatal if swallowed and enters airways.	
H319 Causes serious eye irritation. H371 May cause damage to organs (organs, exposure route). H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. P210 Keep away from heat, sparks, open flames and hot surfaces No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe vapour or dust. P261 Avoid breathing vapour or dust. P264 Wash hands and other contacted skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment.	H315	Causes skin irritation.	
H371 May cause damage to organs (organs, exposure route). H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. P210 Keep away from heat, sparks, open flames and hot surfaces No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe vapour or dust. P261 Avoid breathing vapour or dust. P264 Wash hands and other contacted skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment.	H317	May cause an allergic skin reaction.	
H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. P210 Keep away from heat, sparks, open flames and hot surfaces No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe vapour or dust. P261 Avoid breathing vapour or dust. P264 Wash hands and other contacted skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment.	H319	Causes serious eye irritation.	
H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. P210 Keep away from heat, sparks, open flames and hot surfaces No smoking. R233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe vapour or dust. P261 Avoid breathing vapour or dust. P264 Wash hands and other contacted skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment.	H371	May cause damage to organs (organs, exposure route).	
H412 Harmful to aquatic life with long lasting effects. P210 Keep away from heat, sparks, open flames and hot surfaces No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe vapour or dust. P261 Avoid breathing vapour or dust. P264 Wash hands and other contacted skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment.	H410	Very toxic to aquatic life with long lasting effects.	
P210 Keep away from heat, sparks, open flames and hot surfaces No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe vapour or dust. P261 Avoid breathing vapour or dust. P264 Wash hands and other contacted skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment.	H411	Toxic to aquatic life with long lasting effects.	
P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe vapour or dust. P261 Avoid breathing vapour or dust. P264 Wash hands and other contacted skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment.	H412	Harmful to aquatic life with long lasting effects.	
P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe vapour or dust. P261 Avoid breathing vapour or dust. P264 Wash hands and other contacted skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment.	P210	Keep away from heat, sparks, open flames and hot surfaces No smoking.	
P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe vapour or dust. P261 Avoid breathing vapour or dust. P264 Wash hands and other contacted skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment.	P233	Keep container tightly closed.	
P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe vapour or dust. P261 Avoid breathing vapour or dust. P264 Wash hands and other contacted skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment.	P240	Ground/bond container and receiving equipment.	
P243 Take precautionary measures against static discharge. P260 Do not breathe vapour or dust. P261 Avoid breathing vapour or dust. P264 Wash hands and other contacted skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment.	P241	Use explosion-proof electrical, ventilating and lighting equipment.	
P260 Do not breathe vapour or dust. P261 Avoid breathing vapour or dust. P264 Wash hands and other contacted skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment.	P242	Use only non-sparking tools.	
P261 Avoid breathing vapour or dust. P264 Wash hands and other contacted skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment.	P243	Take precautionary measures against static discharge.	
P264 Wash hands and other contacted skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment.	P260	Do not breathe vapour or dust.	
P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment.	P261	Avoid breathing vapour or dust.	
P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment.	P264	Wash hands and other contacted skin thoroughly after handling.	
P273 Avoid release to the environment.	P270	Do not eat, drink or smoke when using this product.	
	P272	Contaminated work clothing should not be allowed out of the workplace.	
Near protective glaves/ave protection/face protection	P273	Avoid release to the environment.	
rzou vvear protective gloves/eye protection/lace protection.	P280	Wear protective gloves/eye protection/face protection.	

Version:





SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

Product: FRAGRANCE FF1906, 10% \$190638710%

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.		
IF ON SKIN: Wash with plenty of soap and water.		
IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.		
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.		
IF exposed or if you feel unwell: Call a POISON CENTRE or doctor/physician.		
Do not induce vomiting.		
If skin irritation occurs: Get medical advice/attention.		
If skin irritation or rash occurs: Get medical advice/attention.		
If eye irritation persists: Get medical advice/attention.		
Take off contaminated clothing and wash before reuse.		
Wash contaminated clothing before reuse.		
In case of fire: Use carbon dioxide, dry chemical, foam for extinction.		
Collect spillage.		
Store in a well-ventilated place. Keep cool.		
Store locked up.		
Dispose of contents/container to approved disposal site, in accordance with local regulations.		
Skin Corrosion / Irritation Category 2		
Sensitization - Skin Category 1B		
Specific Target Organ Toxicity (Single Exposure) Category 2		

The information in this safety data sheet is to the best of our knowledge true and accurate but all data, instructions, recommendations and/or suggestions are made without guarantee.